

**Mini PC**

# SLIM PC SPC 915M 1H 479

**Full Function System Supported**  
**High Performance,Ultra Low Noise**  
**Low Power Consumption**

## Features

- Support Intel Pentium M and Celeron M CPU up to 2.13GHz
- Intel 915GME / ICH 6M
- Thermal Control Technology
- On-board 10/100 LAN, 1394, USB 2.0
- Ultra low noise and low power consumption
- Support standard 2.5" hard disk
- Power in: DC 12V
- 5.7"(W) x 9.8"(D) x 1.65"(H) (14.6 x 25 x 4.2 cm)



## Applications

- Car, Truck and Mobile PC
- NetPC, Set Top Box, Messaging Solution Controller
- Thin Client Applications, Diskless workstation
- Industrial System Controller, Control Center, Data Center
- Best fit Kiosk, Self-Service Systems, POS Systems, VoD, VoP ...etc.
- Application Server, File Server, Game Server, Printer Server ...etc.

GEDO-TEC Elektronik GmbH  
Goethestr. 28  
65582 Diez

Tel. 0 64 32 / 16 54 Fax 0 64 32 / 6 11 08  
E-Mail mail@gedotec.de



GEDO-TEC Electronic, Inc.  
412 North White Street  
Lancaster, SC 29721  
Telephone + Fax (803) 313-5858  
E-Mail mail@gedotec.com

**Mini PC**

# SLIM PC SPC 915M 1H 479

## Intel Pentium M and Celeron M

### Detail Specifications

- **Processor** Support Socket 479 (Intel Pentium M and Celeron M)  
CPU up to 2.13GHZ.
- **Memory** Support SO DIMM, DDR II 400/533 X 1
- **Core Logic** Intel 915GM / ICH 6M (North / South)
- **Video** Intel Graphics Media Accelerator 900
- **Audio** Software AC '97 Audio CODEC
- **LAN** Built-in high speed Ethernet 100/10Mbps LAN controller
- **FireWire** Built-in OHCI 1394a 1.1 compliance  
Support up to 400Mb transfer rate
- **IDE** One Independent ATA-100/66/33 support for CD-ROM SATA support
- **Hardware Monitor** System, processor temperature, voltage and fan speed monitor  
Auto Thermal FAN speed control
- **Power Management** ACPI 1.0b compliance and OS direct power management  
Wake-on event: RTC/USB Keyboard/Modem/LAN/Keyboard/Mouse
- **Switch and Jumpers**
  - Front Panel:** 1 x IEEE 1394 Firewire port, 1 x USB 2.0 / 1.1 Port  
1 x MIC Port, Ear Phone output Jack  
Power-on button, Reset button, Power-on and HDD LED
  - Back Panel:** 1 x RS232 COM port, 1 x RJ45 10/100Mb Fast Ethernet  
1 x Line-Out output Jack, 2 x USB 2.0 / 1.1 Ports  
1 x Single Link DVI-I
- **Dimension & Weight** 14.6 x 25 x 4.2 cm
- **AC Adaptor** Input 100~240V AC Universal Output 12V DC power adapter
- **Storage Devices** Support Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo  
Support all 2.5" SATA hard drive

