

Mini PC

SLIM PC SPC 915 2H 775

Features

- Fully functional P4/ Intel LGA 775 up to 3.0Ghz w/2M L2 Cache
- Intel 915GV / ICH 6, supporting 800MHz FSB
- Fully support Intel Hyper Threading Technology
- On-board 10/100 LAN, USB 2, 1394.
- Ultra low noise and low power consumption
- Support standard 3.5" hard disk
- 5.8"(W) x 10"(D) x 2.75"(H) (14.8 x 25.4 x 7 cm)

Applications

- Home Entertainment Center
- Gateway, Router, Transportable PC
- Personal Desktop, Office System
- Industrial, Control, Data Collection, Data Center
- Application Server, File Server, Game Server, ...etc.



GEDO-TEC Elektronik GmbH
Goethestr. 28
65582 Diez

Tel. 0 64 32 / 16 54 Fax 0 64 32 / 6 11 08
E-Mail mail@gedotec.de



GEDO-TEC Electronic, Inc.
412 North White Street
Lancaster, SC 29721

Telephone + Fax (803) 313-5858
E-Mail mail@gedotec.com

Mini PC

SLIM PC SPC 915 2H 775

Intel Pentium 4 Processor LGA 775

- **Processor** Support Intel **LGA 775** Pentium 4 CPU up to 3.0GHZ.
- **Memory** Support Dual-Channel **DDR II 400/533** Maximum up to 2 GB
- **Core Logic** **Intel 915G** / ICH 6(North / South)
- **Video** Intel Graphics Media Accelerator 900
- **Audio** Software AC '97 Audio CODEC
- **LAN** Built-in high speed Ethernet 100/10Mbps LAN controller
- **FireWire** Built-in OHCI 1394a 1.1 compliance
Support up to 400Mb transfer rate
- **USB 2.0** Integrated 4 independent OHCI controller supporting USB 1.1 ports
- **IDE** Dual Independent ATA-100/66/33 support
Support up to 4 IDE devices on dual channel
- **Hardware Monitor** System, processor temperature, voltage and fan speed monitor
Auto Thermal FAN speed control
- **Power Management** ACPI 1.0b compliance and OS direct power management
Wake-on event: RTC/USB, Keyboard/Modem/LAN/Keyboard/Mouse
- **Switch and Jumpers**
 - Front Panel:** 1 x IEEE 1394 Firewire port, 1 x USB 2.0 / 1.1 Port
1 x MIC Port, Ear Phone output Jack
Power-on button, Reset button, Power-on and HDD LED
 - Back Panel:** 1 x RS232 COM port, parallel printer port
1 x RJ45 10/100Mb Fast Ethernet, 1 x Line-Out output Jack
2 x USB 2.0 / 1.1 Ports, 1 x 15 pin VGA
- **Dimension & Weight** 14.8 x 25.4 x 7.1 cm 2.5KG (fully equipped)
- **AC Adaptor** Input 100~240V AC Universal Output **19V DC** power adapter
- **Storage Devices** Support Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo
Support all **3.5" standard IDE hard drive**, ATA-100/66/33

